

### REMARKS

Applicants request favorable reconsideration and allowance of this application in view of the foregoing amendments and the following remarks.

Claims 1-52 are pending in this application, with Claims 1, 18, 35, 36, 44, and 52 being independent.

Claims 1-13, 15, 17-30, 32, and 34-52 have been amended. Applicants submit that support for the amendments can be found in the original disclosure and therefore no new matter has been added.


Applicants appreciate the indication that the application is in condition for allowance except for informalities. The claims have been amended to address the Examiner's objections to the claim language. Favorable consideration is requested.

Also, a substitute specification is attached hereto, as required by the Examiner, together with a marked-up copy of the specification showing the amendments. The specification has been amended in view of the Examiner's comments. Applicants submit that no new matter has been added. In particular, the Examiner will note that "is over" has been amended to read --is not over-- at page 15, line 19 of the *original* specification. Applicants submit that one of ordinary skill would readily appreciate from the context that the word "not" was inadvertently omitted, and therefore the correction of this typographical error does not constitute new matter.

In view of the foregoing, Applicants submit that this application is in condition for allowance. Issuance of a Notice of Allowance is respectfully requested.

Applicants' undersigned attorney may be reached in our Washington, D.C. office by telephone at (202) 530-1010. All correspondence should be directed to our below-listed address.


Respectfully submitted,

A handwritten signature in black ink, appearing to read "B. L. Klock", written over a horizontal line.

Attorney for Applicants  
Brian L. Klock  
Registration No. 36,570

FITZPATRICK, CELLA, HARPER & SCINTO  
30 Rockefeller Plaza  
New York, New York 10112-3800  
Facsimile: (212) 218-2200  
BLK/lmj

DC\_MAIN 191586v1



MARKED-UP COPY OF SPECIFICATION

**IMAGE PROCESSING APPARATUS, IMAGE PROCESSING  
METHOD AND A COMPUTER PROGRAM PRODUCT FOR  
JUDGING WHETHER IMAGE DATA INCLUDE SPECIFIC  
INFORMATION RELATED TO COPY PROTECTION**

5

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to an image processing apparatus, an image processing method and a computer program product for judging whether image data include specific information related to copy protection.

10

Description of the Related Art

15

In connection with color copying machines, ~~it has been considered to implement~~ implementing an image recognition processing function to prevent counterfeiting of a copy-prohibited object, such as a banknote or valuable securities has been considered. One drawback of color copying machines is that they are expensive stand-alone devices. More recently, high quality copying has been attained using less expensive computers, ~~and computer peripheral apparatus~~ apparatuses such as a color scanner and a color printer, and image processing software to edit an input and output image. A need has ~~therefore~~ developed for using an image recognition processing function to prevent counterfeiting of a banknote and valuable securities for an inexpensive color image processing system using a color scanner and printer.

20

25

There are some known judging methods for judging whether an original is a copy-prohibited object or not. An original is judged based on a color spectrum distribution of image data (R,G,B data for each pixel)

generated by scanning the original, and a comparison of the color spectrum distribution with copy-prohibited object data stored in a ROM, or based on a comparison of an image pattern of a part of the original(or the entire original) with a copy-prohibited object pattern stored in a ROM. The result of the judging is an evaluation value as to whether the original is a copy-prohibited object or not.

It is recently possible to make a copy-prohibited object by using a technology called digital watermark. The copy-prohibited object is altered to include information indicating whether the object is a copy-prohibited object. The process of making the copy-prohibited object is as follows. First, second digital information (sub-information) ~~is attached~~ indicating a that the object is copy-prohibited ~~object is attached~~ to digital image data as the first digital information (main-information). Next, a printed document is made from the digital image data ~~with its~~ including the attached second information. Of course, the second digital information indicating a that the object is copy-prohibited ~~object can be detected from the digital image data with its attached second digital information,~~ as a characteristic of the digital watermark. It is possible to detect the second digital information indicating a that the object is copy-prohibited ~~object~~ from newly-created image data which is created from the printed document by an image reading apparatus (e.g., a color scanner). This technology is called digital watermark and is increasingly used for prohibiting illegal copying of printed material.

In view of widespread use of computer peripherals to make color ~~copier~~ copies, a judging process chiefly made of software for a copy-prohibited object is preferable to a hardware one comprising many electrical circuits. Such a software process, ~~however, uses~~ however, uses too much processing power and takes too long ~~a time~~ to judge whether an image is of a copy-prohibited object or not and to process the image.

SUMMARY OF THE INVENTION

An object of the present invention is to address the above situation.

5 One particular object of the present invention is to provide an image processing apparatus and method and a computer program product that can avoid unnecessary processing and can provide a faster judgment of whether or not an object is copy-prohibited **faster**.

10 Another object of the present invention is to provide an image processing apparatus and method and a computer program product that have a new function not known before.

15 According to one aspect, the present invention, which achieves these objectives, relates to image processing in which an image resolution of a input image data is compared to information of predetermined standard resolution and the image data is judged to determine whether it includes specific information related to copy protection, with wherein whether or not to perform the judging is being controlled not to work based on the basis of the result of the comparing means comparison.

20 Because the control technique of the present invention controls not to work whether or not to perform the judgment based on the basis of the result of the comparing means comparison, the control technique according to the invention provides an efficient judging processing, since no judgment is performed on low resolution image data which is not so prone to counterfeiting.

25 The foregoing and still other objects, features and advantages of the present invention will become fully apparent from the following description to be taken in conjunction with the attached drawings.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram which shows the image processing apparatus of this ~~suggestion~~ invention.

5 FIG. 2 is a diagram which shows one embodiment of a ~~a~~ an image processing system of the present invention.

FIG. 3 is a block diagram that shows the main portion of FIG. 2.

FIG. 4 is a flow chart which shows the process sequence by using the construction of FIG. 2 and FIG. 3.

10 FIG. 5 is a flow chart which shows the process sequence of a third embodiment.

FIG. 6 is a flow chart which shows a modification of the process sequence of FIG. 4.

15 FIG. 7 is a flow chart which shows a modification of the process sequence of FIG. 4.

FIG. 8 is a flow chart which shows a modification of the process sequence of FIG. 5.

FIG. 9 is a flow chart which shows a modification of the process sequence of FIG. 5.

20 FIG. 10 is a diagram which shows a ~~six~~ sixth embodiment of ~~an~~ the image processing system of the present invention.

FIG. 11 is a block diagram that shows the main portion of FIG. 10.

### DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 FIG. 1 is a block diagram which shows an image processing apparatus of this ~~suggestion~~ invention.

Input image data control means 110 controls a resolution of an image which is read by image data source 120 as an image scanner. Image

data generating means 130 generates image data of an image resolution which is controlled by input image data control means 110. Memory 140 stores the image data generated by image data generating means 130. Data attaching means 150, which is controlled by main control means 200 based on the image resolution controlled by input image data control means 110, attaches digital data to the image data stored in memory 140. Image character recognition means 160, which is controlled by main control means 200 based on the image resolution controlled by input image data control means 110, judges whether the image data stored in memory 140 belongs to a copy-prohibited object image.

Recognition information output means 170 outputs a recognition result of the image character recognition means 160. Recognition information receiving means 180 displays the recognition result on a display or the like, and receives the recognition result information and informs the image processing apparatus's user that an original based on said image data is a copy-prohibited object image. Image data output means 190 outputs sequentially an output image.

Each function block in FIG. 1 ~~works as~~ has the following description. Image data generating means 130 generates image data of a resolution which is indicated from an indicating means (unshown) of input image data control means 110 and is based on a preset image on image data source 120 and an indication by ~~an~~ a user of the image ~~process~~ processing apparatus. Information of the image resolution indicated by a user of the image ~~process~~ processing apparatus is output to main control means 200 at the same time. Main control means 200 ~~control~~ controls data attaching means 150, ~~and~~ image character recognition means 160 and recognition information output means 170 based on the information of the image resolution output from input image data control means 110.

(The first embodiment)

Information indicating a that an object is copy-prohibited object ~~image~~ is attached to an original by using a technology called digital watermark in one preferable embodiment of this invention.

5 An original of the copy-prohibited object is formed by printing  
~~a printing object from the~~ image data ~~to which is~~ with the attached the  
information indicating that the object is a copy-prohibited object. The digital  
image data, with its attached information indicating that the object is copy-  
prohibited ~~object~~, is made by attaching second digital information indicating  
10 that the object is copy-prohibited object to the first digital information which  
is a source of the printing object. The digital watermark is ~~possible to~~ may be  
any kind of digital watermark, such ~~such~~ as one attached to a specific  
frequency of image information as invisible information or visible information  
~~but that is~~ difficult for human eyes to see, like yellow dots.

15 ~~A~~ In an inexpensive color scanner or printer, it is preferable to  
carry out a counterfeit prevention of a copy-prohibited object less ~~expensive~~  
~~than~~ expensively than in a comparatively expensive color copying machine as  
stated above. It is an effective answer to judge the copy-prohibited object by  
using a software process, but the software judging process has a problem  
20 related to ~~a process~~ processing speed. Accordingly, the present invention  
checks the possibility that of whether a printing image based on an original is  
could be used as a counterfeit, in accordance with image resolution. The  
possibility is the degree of risk that someone ~~mistakes~~ would mistake the  
counterfeit for a genuine one.

25 The following is a detailed explanation, which is made with  
reference to the drawings, of the preferred embodiments of this invention.  
FIG.2 shows one embodiment of an image processing system of the present  
invention. Image scanner 1 is an image input apparatus and a personal  
computer 2 processes image data input by image scanner 1. Cable 3 connects  
30 image scanner 1 and personal computer 2 and communicates the image data.



FIG. 3 is a block diagram that shows the main portion of FIG.

2. CPU 11 is a central processing unit, and RAM 12 is random access memory and ROM 13 is read only memory. Display control unit 14 controls display 15 and operation input unit 16 is a keyboard or a mouse. Connection I/O 17 is used for connecting operation input unit 16 to the image processing system. External memory unit 18 is a hard disk or a memory card etc. Connection I/O 19 is used for connecting external memory unit 18 to the image processing system. Bus 20 is used for ~~communication~~ communicating image data or ~~another other~~ data. Image scanner 21 is the same as image scanner 1 in FIG. 2. Connection I/O 22 is used for receiving image data from image scanner 21 and sending control signals to image scanner 21. Interface unit 23 is a communication unit like a network.

FIG. 4 is a flow chart which shows a process sequence based on performing a process of the system shown in blocks of FIG. 2 and FIG. 3. A program ~~which that~~ describes the process sequence of FIG. 4 is stored ~~on in~~ ROM 13 in advance or ~~on in~~ external memory unit 18 and then the program is moved into RAM 12. CPU 11 executes the program to ~~execute perform~~ the process of this embodiment by software processes. The program is preferably a part of a scanner driver.

Reading image resolution, designated by the image system user, is stored ~~on in~~ RAM 12 in step 10. In step 20, CPU 11 judges whether the designated image resolution {Rin} is ~~not as high as~~ less than a predetermined first standard resolution {T1}, e.g. 100 dpi [dot/inch]. This process is the first judgment. ~~In the case~~ If the designated image resolution {Rin} is ~~not as high~~ as less than the predetermined first standard resolution {T1}, ~~[[,]]~~ the process flows to step 40. On the other hand, ~~if in the case~~ the designated image resolution {Rin} is as high as the predetermined first standard resolution {T1}, the process flows to step 30. As a result, a judgment of whether ~~which~~ a scanned image is of a copy-prohibited object ~~image does not work is not performed~~ when the scanned image's resolution is ~~not as high as~~ less than a predetermined resolution since ~~an a~~ printout of the scanned image is useless as

a counterfeit. It is ~~fast~~ faster to print an image ~~that~~ when the image resolution is ~~not as high as~~ less than the first standard density ~~since~~ because the judgment of whether the object is copy-prohibited is not executed.

In step 30, CPU 11 judges whether the designated image resolution {Rin} is ~~not as high as~~ less than the predetermined second standard resolution {T2}, e.g. 300 dpi [dot/inch]. This judgment is a second judgment. ~~In the case~~ If the designated image resolution {Rin} is ~~not as high as~~ less than the predetermined second standard resolution {T2}, the process flows to step 41. On the other hand, ~~if in the case~~ the designated image resolution {Rin} is as high as the predetermined second standard resolution {T1}, the process flows to step 60. It can be expected that a counterfeiter who scans a copy-prohibited object ~~image~~ designates high resolution scanning. Accordingly, judgment as to whether a scanned image is of a copy-prohibited object ~~image~~ executes when the scanned image is has a high resolution.

In step 40 or 41, CPU 11 judges that the image data of that image resolution is a low risk of counterfeiting and indicates, through the connection I/O 22, that the color image scanner 21 is scanning ~~a~~ an original on the flatbed ~~by~~ at the user's designated image resolution. The image scanner scans the original. The image data based on the original is sent and stored ~~on~~ in RAM 12 through the connection I/O 12. After step 40, the process of FIG. 4 flows to step 90. After step 41, the process of FIG. 4 flows to step 50.

In step 50, the image resolution is not high enough and is not suitable for inputting a vivid copy-prohibited object, but CPU 11 takes measures to prevent a counterfeit of the copy-prohibited object by way of caution. ~~Concretely~~ Specifically, CPU 11 attaches the ~~product's~~ product number of personal computer 2 or color image scanner 1 and the user ID information to the image stored ~~on~~ in RAM 12. The attached information is registered when a driver of the color image scanner 1 is installed. If the image stored ~~on~~ in RAM 12 is printed or is output ~~a~~ to an external apparatus through a network, it is thus possible to identify the person or apparatus that scanned the copy-prohibited object ~~image~~ by using the attached information. The

attachment is performed by the technology ~~is called~~ of digital watermark.  
After step 50, the process of FIG. 4 flows to step 90.

In step 60, since there is a possibility of inputting ~~of~~ the copy-prohibited object ~~image~~ as a vivid image, CPU 11 judges ~~the~~ that image data  
5 of ~~the~~ that image resolution is has a high risk of counterfeiting and performs  
extraction of digital watermark data attached to the copy-prohibited object  
~~image~~ from the image stored ~~on~~ in RAM 12. CPU 11 indicates, through  
connection I/O 22, to color image scanner 21 ~~scanning-a~~ to scan an original on  
the flatbed ~~by~~ at a lower image resolution than the user's designated one.  
10 Color image scanner 21 scans the original ~~by~~ at the lower image resolution.  
The image data generated by the scanning is sent to RAM 12 through the  
connection I/O 22. This scanning is carried out by using a well-known  
function of a color image scanner driver. After step 60, the process of FIG. 4  
flows to step 70.

15 In step 70, CPU 11 judges whether the lower resolution image  
data generated by the scanning is ~~the~~ of a copy-prohibited object ~~image~~ or not.  
~~In the case~~ If CPU 11 judges that the lower resolution image data belongs to  
~~the~~ a copy-prohibited object ~~image~~, the process flows to step 80. On the other  
hand, ~~if in the case~~ CPU 11 judges that the lower resolution image data is not  
20 of a copy-prohibited object ~~image~~, the next process is step 42. Step 42 is the  
same as step 40 or 41, and the process flows thereafter to step 90.

In Step 80, the lower resolution image data generated by the  
scanning is output as a processed image. ~~Concretely~~ Specifically, the lower  
resolution image data generated by the scanning is output 1) after converting  
25 color or changing image size, ~~or/and~~ and/or 2) after attaching any symbol or  
figure as a processed image. The processed image is not equal to the scanned  
image data.

It is easy to make the processed image from the image stored ~~on~~  
in RAM 12 by working using a well-known image processing program module  
30 ~~correspond~~ corresponding to 1) and 2) under CPU 11's control. The  
processed image is output to external memory unit 18 as an image data file

through the connection I/O 19. The process terminates when step 80 has finished.

5 In step 90, the image data scanned in step 42 is output to external memory unit 18 as a an image file through the connection I/O 19, when CPU 11 judges that the lower resolution image data generated by the scanning is not of a copy-prohibited object ~~image~~. The process terminates when step 90 has finished.

10 The original as a print document, which is made from the digital image data with attached information indicating a that the object is copy-prohibited ~~object image~~ as a digital watermark, is scanned by color image scanner 21. The judgment of whether the object is copy-prohibited ~~object image~~ in step 80 is performed by extracting the digital watermark from the scanned image data.

15 In step 80, it is possible to select another process in which the image data generated by the scanned image is not output at all. As a result, the image of the copy-prohibited object ~~image can not cannot~~ be input in the first place. Of course, it may be good to give warning of indicating that the original is copy-prohibited ~~object image is an original~~. The warning is displayed on the display 15 through display control unit 14. The warning has the advantage to  
20 stop of stopping mischief and ~~mistake~~ preventing the mistake of using a copy-prohibited object ~~image~~ for the original.

25 It is possible to prevent a counterfeiter from reading a copy-prohibited object ~~image~~ by high image resolution. Additionally, a process speed of this embodiment's image processing system which judges whether an object is a copy-prohibited ~~object image~~ by using software and a CPU is faster because a judgment of whether the object is copy-prohibited ~~object image~~ is not performed for an image read with low image resolution. This embodiment's image processing system does not judge an image read with middle range resolution because a possibility of reading a copy-prohibited  
30 object ~~image~~ is not high enough, and then the middle range resolution image is

attached with information. It is thus possible to stop the software judgment from consuming too much time.

[Second embodiment]

5 The judgment of a whether an object is copy-prohibited ~~object~~  
~~image~~, in step 70 of the first embodiment, is performed for using photo  
electrical converted image data generated from a print ~~object~~ object's added  
information, using digital water mark, to indicate whether ~~indicating~~ the object  
is copy-prohibited ~~object~~ image.

10 For the judgment of a whether an object is copy-prohibited  
~~object image~~, in step 70, it is possible to ~~replace~~ use another method. For  
example, an original is may be judged based on a color spectrum distribution  
based on image data (R,G,B data for each pixel) generated by scanning the  
original and a comparison of the color spectrum distribution with copy-  
prohibited object data stored in a ROM or a comparison of an image pattern of  
15 a part of the original (or the entire original) with a copy-prohibited object  
pattern stored in a ROM. The result of the judging is an evaluation value as to  
whether the original is a copy-prohibited object or not. ~~An original is judged~~  
~~by comparing a color spectrum distribution based on image data (R,G,B data~~  
~~for each pixel) generated by scanning the original with a copy-prohibited~~  
20 ~~object data stored a ROM or by comparing an image pattern of a part of the~~  
~~original(or the entire original) with a copy-prohibited object pattern stored a~~  
~~ROM. The result of the comparing is a evaluation value which indicates~~  
~~whether the original is a copy-prohibited object image or not.~~

25 In this case, the evaluation value (e.g.,the sum of the absolute  
value of the comparing result or the correlation between the image data  
(pattern) and data (pattern) stored in a ROM) is judged on the basis of a  
predetermined threshold. If the sum of the absolute value of the comparing  
result is not over the predetermined threshold, the original is judged ~~[[as]]~~ to  
be a copy-prohibited object image. If the sum of the absolute value of the  
30 comparing result is over the predetermined threshold, the original is not judged

[[as]] to be a copy-prohibited object ~~image~~. If the correlation is over the predetermined threshold, the original is judged [[as]] to be a copy-prohibited object ~~image~~. If the correlation is not over the predetermined threshold, the original is not judged [[as]] to be a copy-prohibited object ~~image~~.

5 [Third embodiment]

In the first embodiment and second embodiment, if an original ~~image~~ is not judged as a copy-prohibited object ~~image~~, the original image is output without information attached to the original image. It is possible to attach information in to the original image in step 51, which is the same as  
10 step 50[, ] and performed after step 42. A flowchart of this process is shown in FIG. 5. FIG. 5 and FIG. 3 4 are the same except for step 51.

[Fourth embodiment]

In step 30 of the first, second and third ~~embodiment~~ embodiments, if the user-designated image resolution is ~~not as high as~~ less  
15 than the predetermined second standard resolution, the specific data is attached to the image data in step 50. It is possible to replace step 50 with step 71, which is the same as step 70, or to perform both step 50 and step 71.

FIG. 6 is a flowchart which performs the first above-mentioned change to FIG. 4. In step 71, after reading an image in step 41, a judgment of  
20 a whether an object is copy-prohibited ~~object~~ is performed. ~~In the case~~ If CPU 11 judges that the image is of a copy-prohibited object ~~image~~, the process flows to step 80. On the other hand, ~~if in the case~~ CPU 11 judges that the image is not of a copy-prohibited object ~~image~~, the ~~next~~ process flows to step 90. The rest of the steps in FIG. 6 are the same as in FIG. 4.

FIG. 7 is a flowchart which performs the ~~alternate~~ other change mentioned above for Fig. 4. In step 71, after being attached with data in step 50, a judgment of a whether the object is copy-prohibited ~~object~~ is performed  
25 like in step 70. ~~In the case~~ If CPU 11 judges that a read image is of a copy-prohibited object ~~image~~, the process flows to step 80. On the other hand, if in

~~the case~~ CPU 11 judges that the image ~~doesn't~~ is not of a copy-prohibited object ~~image~~, the process flows to step 90. It is possible to reduce process speed ~~without~~ by not first reading the image ~~by~~ at low resolution, because ~~the~~ image resolution is already somewhat lower to begin with in this case. The rest of the steps in FIG. 7 are the same as FIG. 4.

FIG. 8 is a flowchart which performs the first above-mentioned change to FIG. 5. In step 71, after reading an image in step 41, a judgment of a whether an object is copy-prohibited ~~object~~ is performed. ~~In the case~~ If CPU 11 judges that the image is of a copy-prohibited object ~~image~~, the next process is step 80. On the other hand, ~~if in the case~~ CPU 11 judges that the image is not of a copy-prohibited object ~~image~~, the process flows to step 90. The rest of the steps in FIG. 8 are the same as in FIG. 5.

FIG. 9 is a flowchart which performs the other above-mentioned change to FIG. 5. In step 71, after being attached with data in step 50, a judgment of a whether the object is copy-prohibited ~~object~~ is performed like in step 70. ~~In the case~~ If CPU 11 judges that a read image is of a copy-prohibited object ~~image~~, the process flows to step 80. On the other hand, ~~if in the case~~ CPU 11 judges that the image is not of a copy-prohibited object ~~image~~, the process flows to step 90. The rest of the steps in FIG. 9 are the same as in FIG. 5.

#### [Fifth embodiment]

The above-mentioned process of attaching data or judging a whether an object is copy-prohibited ~~object~~ is performed for color scanned image data ~~on the basis of~~ based on user-designated image resolution. The process is not only performed for the color scanned image data, but also for other input image data. The other image input data is input from interface unit 23 shown in FIG. 3 as communication means like a network or a detachable storage medium (e.g., smart media, compact flash, magnetic optical disk) which is connected to a un-shown drive unit of the image process system in FIG. 3 and stores color image data. The attached information, in step 50, is

the network address of the sender apparatus ~~which send that sent the~~ image data through interface unit 23 or the number of the detachable memory ~~in the abovementioned case.~~

5                   The above-mentioned judging program ~~of for determining if an~~ object is copy-prohibited object is included in a communication program (ex. Internet browser soft ware) or a program for obtaining image data from a storage medium.

10                   CPU 11 controls the input image resolution information of stored image data in step 10 in this case. Image data stored on the detachable memory being attached to the un-shown drive unit is read through an I/O unit, which is connected the drive unit of the detachable memory. The image resolution information in step 10 and the image data in ~~step~~ steps 40, 41 and 42 may be input through an interface unit connected to a network like the Internet.

15                   [Sixth embodiment]

                  Image data including the processed image data and the scanned image data is output as an image data file to external memory unit 18 (a hard disk of this image processing system) through the connection I/O 19. However, image data may be output to a color printer or an external apparatus through a network and an interface unit. In this case, the information attached ~~attached information~~ in step 50 is a product number or a network address of a send side apparatus or a receive side apparatus. In this embodiment, a copy-prohibited object judging program includes a program for using communication through a network or printer driver.

25                   FIG. 10 indicates ~~a~~ an example of a an image processing system of this embodiment. Image scanner 101 is an image input apparatus and a personal computer 102 processes image data and outputs processed image data to color printer 104 as a an output apparatus.

30                   FIG. 11 is a block diagram that shows the main portion of FIG. 10. Connection I/O ~~+25~~ 25 connects to an image output apparatus like a color



printer. Other components of FIG. 11 are the same as in FIG. 3. In this case, image output in step steps 80 and 90 in FIGS. 4, 5, 6, 7, 8 and 9 ~~are~~ is replaced with image output to a color printer 24 connected through I/O 25. Image data in step steps 80, 90 may be output through an interface unit connected to a network like the Internet.

[Seventh embodiment]

When the color printer outputs an object image in the sixth embodiment, ~~there~~ information is attached ~~information attached~~ to the object image by using the digital watermark method ~~from~~ in step 50 and step 51. However, ~~It~~ it is possible to attach information like a serial number in a printed image as unknown color information for an image processing system user.

(Other embodiments)

The object of the present invention can also be achieved by providing a storage medium that stores ~~storing~~ program codes for performing the aforesaid processes to a system or an apparatus, reading the program codes with a computer (e.g., CPU, MPU) of the system or apparatus from the storage medium, and then executing the program.

In this case, the program codes read from the storage medium realize the functions according to the above-mentioned embodiments, and the storage medium storing the program codes constitutes the invention.

Further, the storage medium, such as a floppy disk, a hard disk, an optical disk, a magneto-optical disk, CD-ROM, CD-R, a magnetic tape, a non-volatile type memory card, and ROM can be used for providing the program codes.

Furthermore, besides the aforesaid functions according to the above embodiments ~~are~~ being realized by executing the program codes which are read by a computer, the present invention includes a case where an OS (Operating System) or the like working on the computer performs a part or

entire processes in accordance with designations of the program codes and realizes functions according to the above embodiments.

5           The image processing system judges a risk of a read image being used ~~for as~~ a forgery ~~on the basis of~~ based on a user's indicated image reading resolution and reduces a process time for prohibiting forgery which is usually performed for every image even when there is little risk.

          As a result, a process ~~of calculation by~~ using a software for prohibiting forgery is efficient and it is possible to ~~be faster than a~~ increase the overall process speed of the image ~~process~~ processing system ~~totally~~.

ABSTRACT

The present invention, ~~which achieves these objectives,~~ relates to image processing in which an image resolution of a input image data is compared to information of predetermined standard resolution, and the image data is judged to determine whether it includes specific information related to copy ~~protection,~~ with protection. ~~Whether or not to perform~~ judging ~~being is~~ controlled based ~~not to work on the basis of~~ the result of the ~~comparing means~~ comparison. Because the control technique of the present invention controls ~~not to work~~ whether or not to perform the judgment based ~~on the basis of~~ the result of the ~~comparing means~~ comparison, the control technique according to the invention provides an efficient judging processing, since no judgment is performed on low resolution image data which is not so prone to counterfeiting.